




**ECODAILY**

**Daily 4x4 35S17W Chassis Cab**

**Technical Specification**

**IVECO**



### Dimensions

	SWB	MWB
A Wheelbase	3050	3400
B Overall length	4921	5432
C Front overhang	900	900
D Rear overhang	971	1132
E Maximum cab width	2016	2016
H Front axle to body	1616	1616
K Overall height (unladen)	2635	2627
L Frame height at rear	1063	1064
Approach angle (degrees)	51	51
Departure angle (degrees)	33	31
Ground clearance - front	300	300
Ground clearance - rear	300	300
Turning circle (k to k) (m)	12.2	13.4
Turning circle (w to w) (m)	13.2	14.4
Maximum body width - Standard	2200	2200
Maximum body width - Optional	2300	2300
Recommended max body length	2750	3300

### Weights (kg)

Kerb weights are with full fuel tank, oil, water, spare wheel, tools and include driver @ 75kgs. Kerb weights are subject to a manufacturing tolerance of + 5%.

Model	35S17W	35S17W
Wheelbase	3050	3400
GVW	3500	3500
GTW	7000	7000
<b>Plated weights</b>		
Front axle	2250	2250
Rear axle	2800	2800
<b>Kerb weights</b>		
Front axle	1705	1715
Rear axle	785	805
Total	2490	2520
Maximum body & payload	1010	980

## Engine

Fuel	Diesel
Capacity (litres)	3.0
Cylinders	4 (16 valves)
Emission Compliance	EEV
Fuel System	Common rail Generation 2
Power (hp/ kW)	170/ 125
@ rpm	2990-3500
Torque (Nm/ lbft)	400/ 295
@ rpm	1250-2990
Exhaust system	Centre emit
Exhaust with CRT	Standard

## Gearbox

Type	6S400OD
	6 speed
	Synchromesh
	Overdrive
1st gear	5.37 : 1
Top gear	0.79 : 1

## Transfer Box

Type	2 Reductions
ON ROAD	
Normal ratio	1:1
Low ratio	1:1.244
OFF ROAD	
Normal ratio	1:3.115
Low ratio	1:3.866
Total ratios: 24, in combination with gearbox ratios	
ON / OFF Road lever. selection only at speed = 0 mph	
No. of shafts	3
Torque distribution front	32%
Torque distribution rear	68%
All wheel drive	Permanent
Diff Lock	Rear and Centre Front - Optional

## PTO

Gearbox - Side mounted (LHS) Hydrocar	23Z2
Transfer box - 4 variants	
DIN5482 coupling - 150 Nm	
DIN 5482 coupling - 250 Nm	
DIN ISO 14 coupling - 350 Nm	
SAE 1400 coupling - 1900 Nm	

## Performance

Vehicle is limited to 110 kph in standard configuration.  
Optional 120 kph variant is tyre dependent.

**Vehicle performance will vary according to load and terrain.**

## Clutch


Type	Hydraulic
Diameter	280

## Front Drive Axle

Type	Rigid, Single Reduction
Axle ratio	4.87
Diff lock	Option

## Rear Drive Axle

Type	Rigid, Single Reduction
Axle ratio	4.87
Diff lock	Standard



## Suspension

Front	Parabolic - 2 leaf
Rear	Parabolic - 3 leaf
Anti-roll Bar	Front and rear
Shock Absorbers	Front and rear

## Wheels & Tyres

Wheels	6 x 17.5
Tyres Standard	9.5R 17.5 - On/Off Road Tread
Tyres Optional	255/100R16 - Full Off Road Tread

## Electrics

Alternator - std	14v - 110A
Alternator - opt	14v - 140A
Battery	12v - 110Ah
Towing electric socket (13 pin)	Standard

## Brakes

Front / diameter	Disc brakes / 297 mm
Rear / diameter	Drum brakes / 270 mm
ABS + EBD	Standard
Parking brake	On rear axle

## Steering

Power assisted - rack & pinion

## Lighting & Signalling

Halogen headlamps; front fog lamps; twin rear fog lamps; twin reverse lamps

**Fuel Tank** - 90 litres on nearside with locking fuel cap



## Standard Equipment Continued

### Security

Central locking with remote control and door locking management - anti-theft system  
 Engine immobiliser  
 Steering lock

### Chassis

Flat topped heavy duty high tensile reinforced steel c-section frame complete with pedestal body mounting brackets  
 Side mounted spare wheel and carrier  
 Tubular rear under ride guard with off road adjustment

### Construction & Finish

C-section steel longitudinal side members with welded tubular cross members with pressed steel unitary construction body mounted on rubber bushes. Anti-corrosion protection includes full catheporetic dipping with galvanized boxed sections and strategic use of zinc plated panels in vulnerable areas. Protective under seal for all under body cabin area, wheel housings and engine area. Steel bumper and side mouldings.

## Standard Equipment

### Cab

Dual passenger seat with headrests  
 Fully adjustable driver's seat with headrest  
 Large dual storage pockets in doors  
 Three point inertia reel belt on all seats  
 Single piece floor mat  
 Exterior mirrors with integrated wide angle and direction indicators with kerbside observation mirror to nearside  
 2 cup holders  
 Underseat storage  
 Bottle holder  
 Glove compartment with added storage  
 A4 storage compartment  
 Additional in-dash storage  
 Cooled compartment (with opt. air conditioning)  
 Clip holder  
 Windows electrically operated  
 A Pillar grab handles for driver & passenger  
 Low entry driver and passenger exterior step

### Heating & Ventilation

Four speed fan with 5 different distribution modes and cab recirculation  
 Windshield and side window defrost facility  
 Fresh air ventilation when heater turned off

### Dashboard incorporates

Dash-mounted gear lever  
 RDS stereo radio/CD player (with Can security)  
 Provision for tachograph  
 Coolant temperature indicator  
 Speedometer  
 Rev. counter  
 2 DIN drawers which can carry CD Player and/or tachograph - model dependent  
 Comfort dashboard (Standard with CRT) - LCD panel additions include: dual trip function; servicing indicator; door locking function; speed alarm; fuel economy indicator; external temperature display and ice warning indicator are also shown only when climate control is specified.

## Optional Equipment

3 way adjustable passenger seat  
 Air conditioning  
 Alarm system  
 Alternator- heavy duty  
 Ambient air temperature gauge (option with air conditioning)  
 Body builder connectors  
 Engine water heater  
 Exterior mirrors - heated and electrically adjustable  
 Front mudflaps  
 Heated drivers seat  
 Heated and suspended driver seat  
 Heated and suspended passenger seat  
 Long external mirror arm  
 Navigator radio  
 Overhead windscreen storage rack and DIN drawer  
 Pollen filter  
 PVC trim  
 Rear axle ratio options  
 Single passenger seat  
 Sump guard  
 Suspended drivers seat  
 Tachograph - digital  
 Towing hook  
 Vertical exhaust pipe

*For a complete list of Daily options please contact your local Iveco distributor*