



6x2 RIGID
360hp



Image for illustration purposes only.

ENGINE

Power: 360hp (265kW) @ 2,200rpm
Torque: 1,650Nm (168.3Kgm) @ 1,200rpm

TRANSMISSION

12 Speed Automated

MASS RATINGS

GVM: 27,600 kg
GCM: 41,000 kg

WHEELBASE

5,700mm | 6,050mm

KEY FEATURES

Compliant to Euro VI STEP E Emission Standard

GPS Predictive Drive

Advanced Emergency Braking System

Adaptive Cruise Control

Lane Departure Warning

Full LED Headlights with Cornering Fog Lights

7" Infotainment System with Apple CarPlay®, Android Auto®

Climate Control HVAC System

WARRANTY

Standard Warranty

3 Years / 750,000km (whichever occurs first)


MAINTENANCE & REPAIR CONTRACTS (OPTIONAL)

	Maintenance	Friction	Repair
Easy Road	•	•	•

IVECO

ENGINE

Engine Model	Cursor 9
Total Displacement	8,710cm ³
Maximum Power	360hp (265kW) @ 2,200rpm
Maximum Torque	1,650Nm (168.3Kgm) @ 1,200rpm



Injection Type	Direct
Fuel Injection System	Common Rail
Bore & Stroke	117 & 135mm
After-Treatment System	Hi-e SCR After-Treatment System with DOC: Diesel Oxidation Catalyst DPF: Diesel Particulate Filter SCR: Selective Catalytic Reduction CUC: Clean Up Catalyst
Emission Compliance	Euro VI STEP E

TRANSMISSION

Description	Automated Manual Transmission (AMT)	
Make & Model	ZF Traxon 12 TX1810 TD	
Shifter Type	Dash Mounted Electronic Shifter with Column Mounted Sequential Shifter	
Gear Ratios: Hi-Tronix 12TX 2640 TD	1st: 16.69	7th: 3.66
	2nd: 12.92	8th: 2.83
	3rd: 9.93	9th: 2.17
	4th: 7.67	10th: 1.68
	5th: 5.90	11th: 1.29
	6th: 4.57	12th: 1.00
	Rev 1: 15.54	Rev 3: 3.40
	Rev 2: 12.03	Rev 4: 2.64

POWER TAKE-OFF

Rear Engine PTO	Without Rear Engine PTO
Gearbox Power Take-off Opening	Equipped
PTO Control	Equipped with Activation Switch and Electrics

ADBLUE® TANK

Fuel Tank with Lockable Cap	480L
AdBlue® Tank	50L

FUEL SAVING FEATURES

GPS-Predictive Drive	Equipped
Eco-Roll	Equipped
EcoSwitch	Equipped

REAR AXLE RATIO

Rear Axle Ratio	3.08
-----------------	------

PERFORMANCE

Engine RPM @ 100km/h	1,612
Road Speed Limiter	100km/h, Conforms to ADR65
Gradeability ¹ @ Rated GVM	57%
Gradeability ¹ @ Rated GCM	38%

¹This is theoretically calculated.
Actual performance may vary under different conditions.

AXLE & SUSPENSION

Front Axle Model & Type	IVECO 5890/D ON - Axle Drop: 142mm
Front Suspension	Parabolic Suspension with Dampers
FA & Suspension Capacity	8,000kg
FA Group Mass Rating	7,100kg (with tyres)
Front Stabiliser Bar	Diameter ø45mm/Roll Rate: 3,300Nm/Deg
Rear Axle Model & Type	MS 17X - SR Drive Axle + 56082/D - Lazy Axle
Rear Suspension	8 Bellow Air Suspension with ECAS Stroke: Raise/Lower = 100mm/-75mm
Rear Dampers	Equipped
RA & Suspension Capacity	21,000kg
RA Group Mass Rating	21,000kg (with tyres)
Rear Stabiliser Bar	Diameter - Drive: ø50mm/Roll Rate: 5770Nm/Deg Diameter - Lazy: ø55mm/Roll Rate: 5484Nm/Deg
Axle Load Indicator	Equipped (with Pneumatic Suspension Only)
Differential Cross Locks	Equipped
Road Friendly Suspension Certification	RFCN: RF2103

BRAKES & AUXILIARY BRAKES

Type/Control	Full Air/Electronic Braking System (EBS)
	- ABS (Anti-Lock Braking System)
	- ASR (Anti-Skid Regulator)
	- DBI (Direct Brake Integration)
	- BAS (Brake Assistant System)
	- BVR (Brake Lining Wear Adjustment)
	- ARB (Hill Holder) - if Fitted and Only with AMT Gearbox
	- ESC (Enhanced Stability Control)
Front Axle	Ventilated Disc: Diameter 432mm/ Braking Surface : 784cm ²
Rear Axle	Ventilated Disc: Diameter 432mm/ Braking Surface : 784cm ²
Engine Brake with 3 Level Retardation	Equipped
Transmission Intarder	Optional



6x2 RIGID
360hp

CHASSIS

Dimensions	304.4 x 80 x 7.7mm
Chassis Width (at Rear)	771.4mm
Material	Steel
Tensile Strength	610N/mm ²
Exhaust Pipe	Chassis Mounted ATS & Horizontal Pipe
Air Tanks	Steel
Front Tow Hook	Equipped
Towing Cross Member (D=200kN)	Equipped

WHEELS & TYRES

Rim Type	10-Stud Disc Wheel (ISO Type) PCD 335mm Finish: Brushed Alloy
Rim Size	22.5" x 8.25"
Tyre Size	Front and Rear 275 / 70R22.5

SAFETY FEATURES

Electronic Stability Programme (ESP)	Equipped
Anti-Lock Brake System (ABS)	Equipped
Anti-Slip Regulator (ASR)	Equipped
Advanced Emergency Braking System (AEBS)	Equipped
Adaptive Cruise Control (ACC)	Equipped
Lane Departure Warning System (LDWS)	Equipped
Reverse Buzzer	Equipped
Daytime Running Lamp (DRL)	Equipped
ECE-R29 Cab Strength Certification	Equipped
ECE-R93 Front Underrun Protection (FUP)	Equipped

ELECTRICAL & ELECTRONICS

Voltage	24V System
Batteries	2x 12 Volt/170Ah Batteries
Electrical Battery Cutout	Equipped
Battery Position	Horizontal on Side Frame -LHS
Alternator	28Volt/90A
Fleet Management System Data Interface (FMS)	Equipped
Chassis Mounted Jump Start Plug	Equipped
CAN OPEN Bodybuilder Interface	Equipped
LED Headlamp - Low Beam	Equipped
LED Headlamp - High Beam	Equipped
Daytime Running Lamp (DRL)	Equipped
Fog Light with Cornering & Bending	Equipped
LED Rear Lights	Equipped
Provision for Roof Rotating Lights	Equipped with Harness & Switch in Cab
Chassis Mounted Pneumatic Horn	Equipped
7-pin Trailer Connection	Equipped

SERVICE INTERVALS

Engine Oil Change Interval ²	50,000km / 12 Months
---	----------------------

²Based on normal operating conditions and may be reduced when operating under severe conditions.

CAB EXTERIOR

	Low Roof Sleeper Cab (AT)
Cab Type	Optional: High Roof Sleeper Cab (AT) Optional: Low Roof Day Cab (AD)
Cab Tilt Mechanism	Servo Assisted Cab Tilt Mechanism
Cab Mounting	Mechanically Suspended Front and Rear
Windscreen Wipers	Automatic - Rain Sensing 2 Speed with Integrated Washer Nozzles
Front Bumper	Multi-Piece Hybrid (Plastic + Metal) Front Bumper with Foldable Step
Rearview Mirrors	2 x Motorised, Heated Flat Main Mirrors & Convex Spotters 1 x LHS Kerb View & Front View Mirrors
External Sunvisor	Equipped
Roof Spoiler	Optional
Colour	White IC 194

CAB INTERIOR

Seating Capacity	Two
Driver Seat	Fabric, Air Suspended, Heated, 3-Way Adjustable Seat
Passenger Seat	Fabric, Air Suspended, Heated, 3-Way Adjustable Seat
Seat Belt	3-Point Lap/Sash type
Sun Visor & Overhead Consoles	Equipped on Both Driver & Passenger Side
Sleeper Berth with Net Protection - ADR 42 Compliant	Equipped
	7" LCD HD Touch Screen Display
	DAB + AM/FM Radio
	USB Input, Bluetooth® Connectivity
	Smart Phone Mirroring
	-Apple CarPlay®
Multimedia Unit	-Android Auto®
	Voice Recognition
	In Built TomTom Satellite Navigation System
	Reverse/Side Camera Compatible
	USB Charging Ports (TYPE A)
	12 Volt Power Socket
HVAC System	Equipped - with Climate Control
Immobiliser	Equipped - with 3 x Remote Central Lock Keys
Power Windows	Equipped
Cup Holders	Equipped
Interior Lighting	LED Internal Lights
Rollup Sun Blinds for Doors	Equipped
Refrigerator	25L Refrigerator Under the Bunk
Bunk Curtains	Equipped

GENUINE ACCESSORY OPTIONS

-Phone Cradle	- Rubber Floor Mats
-Cameras	- Seat Covers
-Foot Well Liners	- 24 to 12 Volt Voltage Reducer

Please check with IVECO NZ for availability and price.



STEERING

Telescopic & Tilt Adjustable Steering Column	Equipped
Steering Wheel	Soft Touch Steering Wheel with the following: - Controls for the Information Screen - Controls for the Phone - Activation for Voice Recognition - Controls for ACC (Adaptive Cruise Control) - Controls for Radio/Media Volume
Steering Angle	Inside: 52° Outside: 36°

IVECO TELEMATICS

Telematics Hardware	Equipped (GSM & GPS & Antenna & 4G SIM) with Provision for Mobile Cradle.
Smart Connectivity Pack (Included for 5 Years)	Upon Subscription. Features Include: - MYIVECO Smart Report - MYIVECO Web Portal & Mobile App - MYIVECO Vehicle Monitoring & Remote Assistance - MYIVECO Easy Way App

Application: Rigid



DIMENSIONS & WEIGHTS

Wheelbase (A)	5,700mm	6,050mm
Overall Length (B)	11,068	11,653mm
Max Width over Fenders (E)	2,500mm	
Front Axle to Back of Cab - Including Filter (F)	900mm	
Frame Height at End of Frame, Unladen (L)	1,019mm	
Front Overhang (C)	1,410mm	
Rear Overhang (D)	2,658mm	2,658mm
Minimum Ground Clearance (Front) (P)	244mm	
Minimum Ground Clearance (Rear) (Q)	240mm	
Overall Height to Top of Cab, Unladen (K)	3,030mm	
Turning Diameter Kerb to Kerb	21,900mm	22,800mm
Turning Diameter Wall to Wall	23,500mm	24,400mm

Wheelbase (A)	5,700mm	6,050mm
Front Track (M)	2,044mm	
Rear Track (N)	1,820mm	
Approach Angle α (°)	14°	
Departure Angle β (°)	8°	8°
Ramp Angle γ (°)	16°	16°
Total Vehicle Kerb Weight*	8,100kg	8,100kg
Kerbweight on Front Axle*	4,628kg	4,628kg
Kerbweight on Rear Axle*	3,472kg	3,472kg
Gross Vehicle Mass (Plated)	27,600kg	
Gross Combination Mass (Plated)	41,000kg	

Notes:

*Indicative chassis tare mass with Standard options, without fuel, Adblue® and driver. $\pm 3\%$ tolerance apply.

Approximate mass of the optionals: 1. Transmission Intarder: 91kg 2. AD Low roof day cab: -97kg 3. AT Medium roof sleeper cab: 40kg

VERSION: 5 VERSION DATE: 07/2026

IVECO TRUCKS AUSTRALIA LIMITED TRADING AS IVECO TRUCKS NEW ZEALAND.
1 JERRY GREEN ST, WIRI, AUCKLAND 2104, NEW ZEALAND. PHONE: 0800 2 IVECO. WWW.IVECO.CO.NZ

THE INFORMATION IN THIS DOCUMENT WAS CORRECT AT THE DATE OF REVISION. THE DATA IN THIS DOCUMENT IS APPROXIMATE. IF AN EXACT WEIGHT OR DIMENSION IS REQUIRED PLEASE CONTACT IVECO NZ. ALWAYS CONSULT IVECO NZ FOR THE LATEST INFORMATION ON THE VEHICLE BEFORE DECIDING TO PLACE AN ORDER.

OVERSEAS IMAGES AND ILLUSTRATIONS ARE SHOWN THROUGHOUT THIS DOCUMENT AND IMAGES MAY REFER TO EQUIPMENT THAT IS OPTIONAL.
THE MODELS DESCRIBED CAN BE SUBJECT TO MODIFICATIONS WITHOUT ANY NOTICE BY THE MANUFACTURER. IVE3079-AT230S36Y-SS. 04/2024