

# **Tractor**







AD 400T38 TH 4x2

## SPECIFICATIONS

#### **ENGINE**

IVECO CURSOR 13 Displacement: 12,882 cc Power: 380 hp @ 1,500-1,900 rpm Torque: 183 kgm @ 900-1,400 rpm

Diesel, 6 cylinders in line
Unit Pump Injector
Intake: Turbocharger with

Intercooler

#### **PERFORMANCE**

Max. Speed 4X2: 113 (km/hr) 4X2: 113

Gradeability 4X2: 37% @ 44t 6X4: 29% @ 72t

#### CLUTCH

Single Plate Pull Type Clutch Diameter: 430 mm

## GEARBOX

ZF 16 S 2220 TO (Over Drive) 16 Forward & 2 Reverse Pneumatic Splitter Control

#### **BRAKES**

2 independent pneumatic circuits ABS + EBL on rear Duo-Duplex Drum Brakes Mechanical with spring cylinder Emergency Brakes combined with parking brakes Air reservoirs

4X2: 4x20 litres, steel 6X4: 5x20 litres, steel Engine Exhaust Brake Air compressor: 352 cc Air dryer

Trailer Connection 15 pin plug as alternative 7+7 pin

#### **STEERING**

Power assisted

#### SUSPENSION

Front: Parabolic leaf Rear: Semi-elliptic leaf Anti roll bar: Front & rear Shock Absorber: 2 on front & rear

#### **CHASSIS**

Ladder construction type, pressed steel side members and riveted and bolted cross members

#### **AXLES**

Front: Rigid

Rear: 4x2: Single reduction 6x4: Hub reduction with differential lock Axle Gear Ratio 4x2: 4.11 6x4: 4.23

#### **TIRE**

13R22.5 Tubeless

#### **ELECTRICAL SYSTEM**

Alternator: 28v, 90A Starter: 24v, 5.5kW Batteries: 2 x 12v, 170Ah

#### **FUEL TANK**

300lt., steel with lockable cap


### САВ

Air-conditioned
Air suspended 3 way driver's seat
Cruise control
Variable speed limiter
Steel front bumper
Radiator Anti-Clogging Screen
Battery Insulator
Electronic Speed Limiter
Auto Adjust: Belt, Brake, Clutch

Fuel Water Separator

## AD 720T38 TH 6x4

Cursor 13 - 380 HP (283 KW)



## DIMENSIONS (mm)

	4X2	6X4
Wheelbase	3,500	3,200 + 1,380
Cab Width	2,550	2,550
Cab Height	3,101	3,108
Frame Height at Rear	1,230	1,094
Overall Length	5.971	6.844

## WEIGHTS (kg)

	4X2	6X4
Gross Combination Weight	44,000	72,000
Gross Vehicle Weight	21,000	34,000
Axle Capacity (Front)	8,000	8,000
Axle Capacity (Rear)	13 000	26,000

## **Columbian Motors Corporation**

"Your Ultimate and Dependable Partner"

### Assembly Plant:

Km. 42 Bo. Dita, City of Sta. Rosa Laguna 4026 (049) 531-2030 to 32 info@santarosaph.com

#### Manila Office:

Andrews Avenue, Pasay City 1300 (02) 852-2441 • 854-0843 marketing@columbianph.com

### Davao Office:

Bo. Pampanga, Lanang, Davao City 8000 (082) 235-0263 partsdvo@columbianph.com

Note: Columbian Motors Corporation reserves the right to change the vehicle specifications without prior notice

The picture is used for presentation only, It may vary from actual unit.